Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	sources					
Supplier's name or trade mark: Nikkarien Oy						
Supplier's address: Teollisuustie 6 H8 02880 Veikkola						
Model identifier: Led Strip / Led54RGB						
Type of light source:						
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap-type		External adapter				
(or other electric interface)		connection				
Mains or non-mains:		NMLS	Connected light source (CLS):	No		
Colour-tuneable	e light source:	Yes	Envelope:	-		
High luminance	light source:	No				
Anti-glare shield	d:	No	Dimmable:	Yes		
Product parameters						
		Value	Parameter	Value		
		General product p	T	I		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	В		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)			Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2700-6500		
On-mode power (P _{on}), ex- pressed in W		7	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set			
Outer dimen-	Height	12	Spectral power dis-	See image		
sions without	Width	22	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	500	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,281		
		nates (x and y)	0,306		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	1	Survival factor	0,90		
the lumen maintenance factor	1,00				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,55	Colour consistency in McAdam ellipses	0		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0		

(a)'-': not applicable; (b)'-': not applicable;





